



23m Diesel/Electric Spider Lift

MACHINE SPECIFICATION SHEET

TR23

REACH HEIGHT	23.00m
PLATFORM HEIGHT	21.00m
CLOSED LENGTH	5.33m
CLOSED HEIGHT	2.10m
CLOSED WIDTH	0.78m
HORIZONTAL REACH	11.00m
WIDTH MAX WORKING	3.55m
WIDTH MIN WORKING	2.95m
SAFE WORKING LOAD	200kg
WEIGHT	2,900kg
CAGE DIMENSIONS	1.30x0.70x1.10m
GRADEABILITY	31%
CAGE ROTATION	180°
IPAF CATEGORY	1b
SLEW	360°
UP AND OVER CLEARANCE	8.75m
MINIMUM SETUP AREA	2.65x5.33m (WxL)
TRACK SURFACE AREA	N/A
DRIVE SPEED	2.00km/h
MAXIMUM SETUP INCLINE	31%
NO. OUTRIGGER POSITIONS	Multi 4*
POWER	DIESEL/ELECTRIC
FEATURED MODEL	CTE TRACCESS 230



A versatile narrow tracked access platform for hire with a width of 0.78m the CTE TRACCESS 230 spider lift fits through standard doors and narrow entrances. It has an unrestricted working area of 23m reach height and an outreach of 12m with a maximum of 200kg safe working load. The 2.10m jib with 10° working angle and a +/- 320° turret rotation allows you to reach the correct working position easily and safely. Ideal applications for this spider lift includes underbridge maintenance / works, building and construction and facilities management.

The information provided is for guidance only. It may change at any time in accordance with manufacturer's specification. Variable jacking will envelope. Outreach is variable depending on load, angle of rotation and outrigger configuration.

*Narrow, standard, left side, right side.

